







# Decision support

Series/products	Application areas							Features and technical data																
	Hotel and office cleaning	House and home	Garage / Workshop / Hobby	Outside area / coarse dirt	Cleaning large areas and buildings	Operational and machine cleaning	Wet-dry cleaning	Rubber wheels and castors	Noise insulated	Water level detection	Speed controller	Antistatically prepared	Accessory compartment	Brake (y/n)	Max. Power consumption/Watts	Vacuum (mbar, measured at the motor head)	Volume flow (l/s, measured at the motor head)	Max. Container volume/litres	Weight/kg	Reach (including cable and pipe)	Sound volume dB (A)	Filter surface area cm <sup>2</sup>	Page	
 <b>uClean</b>																								
uClean 1420 HK		●	●			●		n	n	y	n	n	y	n	1400	259	69	20	7.8	9.75–10.75	72.5	3600	44	
uClean 1432 HK		●	●			●		n	n	y	n	n	y	n	1400	259	69	32	8.1	9.75–10.75	72.5	3600	44	
uClean 1432 ST			●	●	●	●		n	n	y	n	n	y	n	1400	259	69	32	8.1	9.75–10.75	72.5	3600	45	
uClean LD-1420 HMT	●	●		●		●		y	y	y	2-level	n	y	y	1400	259	69	20	8.0	15.2–16.2	68.5	3600	46	
uClean LD-1432 HMT	●	●		●		●		y	y	y	2-level	n	y	y	1400	259	69	32	8.3	15.2–16.2	68.5	3600	46	
uClean LD-1435 PZ				●	●	●		y	y	y	2-level	n	y	y	1400	259	69	35	9.9	15.2–16.2	68.5	3600	47	
uClean LD-1445 PZ				●	●	●		y	y	y	2-level	n	y	y	1400	259	69	45	12.6	15.2–16.2	68.5	7200	47	
uClean LD-1422 HZ plus		●				●		y	y	y	2-level	n	y	y	1400	259	69	22	9.6	15.2–16.2	69.5	3600	47	
 <b>GS</b>																								
GS 2078 PZ				●	●	●		n	n	y	n	y	n	n	2400	205	108	78	23.5	11.7–12.7	77		48	
GS 3078 PZ				●	●	●		n	n	y	n	y	n	n	3600	205	162	78	26.0	11.7–12.7	79		48	
 <b>eSwift</b>																								
eSwift 1220 HK		●	●			●		n	n	y	n	n	y	n	1200	210	70	20	7.3	6.75–7.75	72.5	3600	53	
eSwift 1232 HK		●	●			●		n	n	y	n	n	y	n	1200	210	70	32	7.4	6.75–7.75	72.5	3600	53	
 <b>Special vacuum cleaners</b> 																								
uClean PA-1455 KFG FW						●		n	n	y	2-level	y	n	y	2200	248	61	55	22.0	18.0–50.0	73	3600	51	
uClean PA-1455 KFG						●		n	n	y	2-level	y	n	y	2200	248	61	55	20.3	18.0–50.0	73	3600	51	
* for large volumes of liquid																								
 <b>TS</b>																								
TS 711 BASIC	●	●						y	y	n	Eco mode	n	y	n	700	210	38	11	4.2	13.0	77		55	
TS 714 RTS HEPA	●	●						y	y	n	Eco mode	n	y	n	700	210	42	14	4.9	13.0	73		55	